



# 2.2M X-Band Shipboard Antenna

## Specifications

Parameter	Performance	
Frequency Range	Receive: 7.25-7.75 GHz	Transmit: 7.90 – 8.40 GHz
Polarization	Receive: LHCP	Transmit: RHCP
Isolation	TX/RX >100	
Power Handling	2000 Watts	
Sidelobe Levels	MIL-STD-188-164A	



### Features:

- Developed for the German Navy F125 Class Frigate
- Upgradable X/Ku and X/Ka-Band Feed Simultaneous Multiband Option
- Low PIM Capability
- High Power Capacity
- High Efficiency Shaped Dual Reflector

### Contact

3311 E. Renner Road, Suite 100  
 Richardson, TX 75082 USA  
 1.469.330.5020  
[multiband@comtechtel.com](mailto:multiband@comtechtel.com)

## About Comtech

Comtech Telecommunications Corp. (Nasdaq: CMTL) designs, develops, produces and markets innovative products, systems and services for advanced communications solutions. The Company sells products to a diverse customer base in the global commercial and government communications markets. For more information visit [www.comtechtel.com](http://www.comtechtel.com).

### Command & Control Technologies™

275 West Street  
 Annapolis, MD 21401 USA  
 Toll Free: 1.800.557.5869  
 Outside US: +1.410.263.7616  
[www.comtech-cct.com](http://www.comtech-cct.com)